

IRF7343



HEXFET® Power MOSFET

- Generation V Technology
- Ultra Low On-Resistance
- Dual N and P Channel MOSFET
- Surface Mount
- Fully Avalanche Rated

Description

Fifth Generation HEXFETs from International Rectifier utilize advanced processing techniques to achieve extremely low on-resistance per silicon area. This benefit, combined with the fast switching speed and ruggedized device design that HEXFET Power MOSFETs are well known for, provides the designer with an extremely efficient and reliable device for use in a wide variety of applications.

The SO-8 has been modified through a customized leadframe for enhanced thermal characteristics and multiple-die capability making it ideal in a variety of power applications. With these improvements, multiple devices can be used in an application with dramatically reduced board space. The package is designed for vapor phase, infra red, or wave soldering techniques.



Absolute Maximum Ratings

| Parameter | Description | Max. | | Units |
|--------------------------------|---|-------------|-----------|------------------|
| | | N-Channel | P-Channel | |
| V_{DS} | Drain-Source Voltage | 55 | -55 | V |
| $I_D @ T_A = 25^\circ\text{C}$ | Continuous Drain Current, $V_{GS} @ 10\text{V}$ | 4.7 | -3.4 | A |
| $I_D @ T_A = 70^\circ\text{C}$ | Continuous Drain Current, $V_{GS} @ 10\text{V}$ | 3.8 | -2.7 | |
| I_{DM} | Pulsed Drain Current ① | 38 | -27 | |
| $P_D @ T_A = 25^\circ\text{C}$ | Maximum Power Dissipation ⑤ | 2.0 | | W |
| $P_D @ T_A = 70^\circ\text{C}$ | Maximum Power Dissipation ⑤ | 1.3 | | W |
| E_{AS} | Single Pulse Avalanche Energy ③ | 72 | 114 | mJ |
| I_{AR} | Avalanche Current | 4.7 | -3.4 | A |
| E_{AR} | Repetitive Avalanche Energy | 0.20 | | mJ |
| V_{GS} | Gate-to-Source Voltage | ± 20 | | V |
| dv/dt | Peak Diode Recovery dv/dt ② | 5.0 | -5.0 | V/ns |
| T_J, T_{STG} | Junction and Storage Temperature Range | -55 to +150 | | $^\circ\text{C}$ |

Thermal Resistance

| Parameter | Description | Typ. | Max. | Units |
|-----------------|-------------------------------|------|------|--------------------|
| $R_{\theta JA}$ | Maximum Junction-to-Ambient ⑤ | --- | 62.5 | $^\circ\text{C/W}$ |

Electrical Characteristics @ T_J = 25°C (unless otherwise specified)

| Parameter | Min. | Typ. | Max. | Units | Conditions | |
|--|------|------|-------|-------|------------|---|
| | | | | | | Parameter |
| V _{(BR)DSS} | N-Ch | 55 | — | — | V | V _{GS} = 0V, I _D = 250μA |
| | P-Ch | -55 | — | — | | V _{GS} = 0V, I _D = -250μA |
| ΔV _{(BR)DSS} /ΔT _J | N-Ch | — | 0.059 | — | V/°C | Reference to 25°C, I _D = 1mA |
| | P-Ch | — | 0.054 | — | | Reference to 25°C, I _D = -1mA |
| R _{DS(ON)} | N-Ch | — | 0.043 | 0.050 | Ω | V _{GS} = 10V, I _D = 4.7A ③ |
| | | — | 0.056 | 0.065 | | V _{GS} = 4.5V, I _D = 3.8A ④ |
| | P-Ch | — | 0.095 | 0.105 | | V _{GS} = -10V, I _D = -3.4A ④ |
| | | — | 0.150 | 0.170 | | V _{GS} = -4.5V, I _D = -2.7A ④ |
| V _{GS(th)} | N-Ch | 1.0 | — | — | V | V _{DS} = V _{GS} , I _D = 250μA |
| | P-Ch | -1.0 | — | — | | V _{DS} = V _{GS} , I _D = -250μA |
| g _{fs} | N-Ch | 7.9 | — | — | S | V _{DS} = 10V, I _D = 4.5A ③ |
| | P-Ch | 3.3 | — | — | | V _{DS} = -10V, I _D = -3.1A ④ |
| I _{DSS} | N-Ch | — | — | 2.0 | μA | V _{DS} = 55V, V _{GS} = 0V |
| | P-Ch | — | — | -2.0 | | V _{DS} = -55V, V _{GS} = 0V |
| | N-Ch | — | — | 25 | | V _{DS} = 55V, V _{GS} = 0V, T _J = 55°C |
| | P-Ch | — | — | -25 | | V _{DS} = -55V, V _{GS} = 0V, T _J = 55°C |
| I _{GSS} | N-P | — | — | ±100 | nA | V _{GS} = ±20V |
| Q _g | N-Ch | — | 24 | 36 | nC | N-Channel I _D = 4.5A, V _{DS} = 44V, V _{GS} = 10V ④ |
| | P-Ch | — | 26 | 38 | | |
| Q _{gs} | N-Ch | — | 2.3 | 3.4 | nC | P-Channel I _D = -3.1A, V _{DS} = -44V, V _{GS} = -10V ④ |
| | P-Ch | — | 3.0 | 4.5 | | |
| Q _{gd} | N-Ch | — | 7.0 | 10 | nC | N-Channel V _{DD} = 28V, I _D = 1.0A, R _G = 6.0Ω, R _D = 28Ω ④ |
| | P-Ch | — | 8.4 | 13 | | |
| t _{d(on)} | N-Ch | — | 8.3 | 12 | ns | P-Channel V _{DD} = -28V, I _D = -1.0A, R _G = 6.0Ω, R _D = 28Ω ④ |
| | P-Ch | — | 14 | 22 | | |
| t _r | N-Ch | — | 3.2 | 4.8 | ns | N-Channel V _{GS} = 0V, V _{DS} = 25V, f = 1.0MHz |
| | P-Ch | — | 10 | 15 | | |
| t _{d(off)} | N-Ch | — | 32 | 48 | ns | P-Channel V _{GS} = 0V, V _{DS} = -25V, f = 1.0MHz |
| | P-Ch | — | 43 | 64 | | |
| t _f | N-Ch | — | 13 | 20 | ns | P-Channel V _{GS} = 0V, V _{DS} = -25V, f = 1.0MHz |
| | P-Ch | — | 22 | 32 | | |
| C _{iss} | N-Ch | — | 740 | — | pF | N-Channel V _{GS} = 0V, V _{DS} = 25V, f = 1.0MHz |
| P-Ch | — | 690 | — | | | |
| C _{oss} | N-Ch | — | 190 | — | pF | P-Channel V _{GS} = 0V, V _{DS} = -25V, f = 1.0MHz |
| | P-Ch | — | 210 | — | | |
| C _{rss} | N-Ch | — | 71 | — | pF | P-Channel V _{GS} = 0V, V _{DS} = -25V, f = 1.0MHz |
| | P-Ch | — | 86 | — | | |

Source-Drain Ratings and Characteristics

| Parameter | Min. | Typ. | Max. | Units | Conditions | |
|-----------------|------|------|-------|-------|------------|---|
| | | | | | | Parameter |
| I _S | N-Ch | — | — | 2.0 | A | |
| | P-Ch | — | — | -2.0 | | |
| I _{SM} | N-Ch | — | — | 38 | A | |
| | P-Ch | — | — | -27 | | |
| V _{SD} | N-Ch | — | 0.70 | 1.2 | V | T _J = 25°C, I _S = 2.0A, V _{GS} = 0V ③ |
| | P-Ch | — | -0.80 | -1.2 | | T _J = 25°C, I _S = -2.0A, V _{GS} = 0V ③ |
| t _{rr} | N-Ch | — | 60 | 90 | ns | N-Channel T _J = 25°C, I _F = 2.0A, di/dt = 100A/μs ④ |
| | P-Ch | — | 54 | 80 | | |
| Q _{rr} | N-Ch | — | 120 | 170 | nC | P-Channel T _J = 25°C, I _F = -2.0A, di/dt = 100A/μs ④ |
| | P-Ch | — | 85 | 130 | | |

Notes:

- ① Repetitive rating; pulse width limited by max. junction temperature. (See fig. 22)
- ② N-Channel I_{SD} ≤ 4.7A, di/dt ≤ 220A/μs, V_{DD} ≤ V_{(BR)DSS}, T_J ≤ 150°C
P-Channel I_{SD} ≤ -3.4A, di/dt ≤ -150A/μs, V_{DD} ≤ V_{(BR)DSS}, T_J ≤ 150°C
- ③ N-Channel Starting T_J = 25°C, L = 6.5mH R_G = 25Ω, I_{AS} = 4.7A.
P-Channel Starting T_J = 25°C, L = 20mH R_G = 25Ω, I_{AS} = -3.4A.
- ④ Pulse width ≤ 300μs; duty cycle ≤ 2%.
- ⑤ Surface mounted on FR-4 board, t ≤ 10sec.




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. Typical Transfer Characteristics




Fig 4. Typical Source-Drain Diode Forward Voltage




Fig 5. Normalized On-Resistance Vs. Temperature




Fig 6. Typical On-Resistance Vs. Drain Current




Fig 7. Typical On-Resistance Vs. Gate Voltage




Fig 8. Maximum Avalanche Energy Vs. Drain Current




Fig 9. Typical Capacitance Vs. Drain-to-Source Voltage




Fig 10. Typical Gate Charge Vs. Gate-to-Source Voltage




Fig 11. Maximum Effective Transient Thermal Impedance, Junction-to-Ambient




Fig 12. Typical Output Characteristics




Fig 13. Typical Output Characteristics




Fig 14. Typical Transfer Characteristics




Fig 15. Typical Source-Drain Diode Forward Voltage




Fig 16. Normalized On-Resistance Vs. Temperature




Fig 17. Typical On-Resistance Vs. Drain Current




Fig 18. Typical On-Resistance Vs. Gate Voltage




Fig 19. Maximum Avalanche Energy Vs. Drain Current




Fig 20. Typical Capacitance Vs. Drain-to-Source Voltage




Fig 21. Typical Gate Charge Vs. Gate-to-Source Voltage






Fig 22. Maximum Effective Transient Thermal Impedance, Junction-to-Ambient

SO-8 Package Outline


Dimensions are shown in millimeters (inches)



| DIM | INCHES | | MILLIMETERS | |
|-----|------------|-------|-------------|------|
| | MIN | MAX | MIN | MAX |
| A | .0532 | .0688 | 1.35 | 1.75 |
| A1 | .0040 | .0098 | 0.10 | 0.25 |
| b | .013 | .020 | 0.33 | 0.51 |
| c | .0075 | .0098 | 0.19 | 0.25 |
| D | .189 | .1968 | 4.80 | 5.00 |
| E | .1497 | .1574 | 3.80 | 4.00 |
| e | .050 BASIC | | 1.27 BASIC | |
| e1 | .025 BASIC | | 0.635 BASIC | |
| H | .2284 | .2440 | 5.80 | 6.20 |
| K | .0099 | .0196 | 0.25 | 0.50 |
| L | .016 | .050 | 0.40 | 1.27 |
| y | 0° | 8° | 0° | 8° |




- NOTES:
1. DIMENSIONING & TOLERANCING PER ASME Y14.5M-1994.
 2. CONTROLLING DIMENSION: MILLIMETER
 3. DIMENSIONS ARE SHOWN IN MILLIMETERS [INCHES].
 4. OUTLINE CONFORMS TO JEDEC OUTLINE MS-012AA
 5. DIMENSION DOES NOT INCLUDE MOLD PROTRUSIONS. MOLD PROTRUSIONS NOT TO EXCEED 0.15 [0.006].
 6. DIMENSION DOES NOT INCLUDE MOLD PROTRUSIONS. MOLD PROTRUSIONS NOT TO EXCEED 0.25 [0.010].
 7. DIMENSION IS THE LENGTH OF LEAD FOR SOLDERING TO A SUBSTRATE.



SO-8 Part Marking

EXAMPLE: THIS IS AN IRF7101 (MOSFET)




IRF7343


International
IR Rectifier

SO-8 Tape and Reel

Dimensions are shown in millimeters (inches)



- NOTES:
1. CONTROLLING DIMENSION : MILLIMETER.
 2. ALL DIMENSIONS ARE SHOWN IN MILLIMETERS(INCHES).
 3. OUTLINE CONFORMS TO EIA-481 & EIA-541.



- NOTES :
1. CONTROLLING DIMENSION : MILLIMETER.
 2. OUTLINE CONFORMS TO EIA-481 & EIA-541.

Data and specifications subject to change without notice.

International
IR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7903

Visit us at www.irf.com for sales contact information. 04/05