

INTERNATIONAL RECTIFIER


INTERNATIONAL RECTIFIER

Data Sheet No. PD-9.444B

T-39-13



REPETITIVE AVALANCHE AND dv/dt RATED* HEXFET® TRANSISTORS



N-CHANNEL

IRFP240
IRFP241
IRFP242
IRFP243

200 Volt, 0.18 Ohm HEXFET TO-247AC (TO-3P) Plastic Package

The HEXFET® technology is the key to International Rectifier's advanced line of power MOSFET transistors. The efficient geometry and unique processing of this latest "State of the Art" design achieves: very low on-state resistance combined with high transconductance; superior reverse energy and diode recovery dv/dt capability.

The HEXFET transistors also feature all of the well established advantages of MOSFETs such as voltage control, very fast switching, ease of paralleling and temperature stability of the electrical parameters.

They are well suited for applications such as switching power supplies, motor controls, inverters, choppers, audio amplifiers and high energy pulse circuits.

Product Summary



Part Number	BVDSS	R _{DSON}	I _D
IRFP240	200V	0.18Ω	20A
IRFP241	150V	0.18Ω	20A
IRFP242	200V	0.22Ω	18A
IRFP243	150V	0.22Ω	18A



FEATURES:

- Repetitive Avalanche Ratings
- Dynamic dv/dt Rating
- Simple Drive Requirements
- Ease of Paralleling

CASE STYLE AND DIMENSIONS



Conforms to JEDEC Outline TO-247AC (TO-3P)
Dimensions in Millimeters and (Inches)

*This data sheet applies to product with batch codes that begin with a digit, i.e. 2A3B
C-483

IRFP240, IRFP241, IRFP242, IRFP243 Devices

INTERNATIONAL RECTIFIER


T-39-13

Absolute Maximum Ratings

Parameter	IRFP240, IRFP241	IRFP242, IRFP243	Units
$I_D @ T_C = 25^\circ\text{C}$ Continuous Drain Current	20	18	A
$I_D @ T_C = 100^\circ\text{C}$ Continuous Drain Current	12	11	A
I_{DM} Pulsed Drain Current ^①	80	72	A
$P_D @ T_C = 25^\circ\text{C}$ Max. Power Dissipation	150		W
Linear Derating Factor	1.2		W/K ^②
V_{GS} Gate-to-Source Voltage	± 20		V
E_{AS} Single Pulse Avalanche Energy ^③	510 (See Fig. 14)		mJ
I_{AR} Avalanche Current ^④ (Repetitive or Non-Repetitive)	20 (See E_{AR})		A
E_{AR} Repetitive Avalanche Energy ^⑤	15 (See I_{AR})		mJ
dv/dt Peak Diode recovery dv/dt ^⑥	5.0 (See Fig. 17)		V/ns
T_J T_{STG} Operating Junction Storage Temperature Range	-55 to 150		°C
Lead Temperature	300 (0.063 in. (1.6mm) from case for 10s)		°C

Electrical Characteristics @ $T_J = 25^\circ\text{C}$ (Unless Otherwise Specified)

Parameter	Type	Min.	Typ.	Max.	Units	Test Conditions
BV_{DSS} Drain-to-Source Breakdown Voltage	IRFP240 IRFP242	200	—	—	V	$V_{GS} = 0\text{V}, I_D = 250\mu\text{A}$
	IRFP241 IRFP243	150	—	—		
$R_{DS(on)}$ Static Drain-to-Source On-State Resistance ^⑦	IRFP240 IRFP241	—	0.12	0.18	Ω	$V_{GS} = 10\text{V}, I_D = 11\text{A}$
	IRFP242 IRFP243	—	0.18	0.22		
$I_{D(on)}$ On-State Drain Current ^⑧	IRFP240 IRFP241	20	—	—	A	$V_{DS} > I_{D(on)} \times R_{DS(on)} \text{ Max.}$ $V_{GS} = 10\text{V}$
	IRFP242 IRFP243	18	—	—		
$V_{GS(th)}$ Gate Threshold Voltage	ALL	2.0	—	4.0	V	$V_{DS} = V_{GS}, I_D = 250\mu\text{A}$
g_{fs} Forward Transconductance ^⑨	ALL	7.3	11	—	S(U)	$V_{DS} \geq 50\text{V}, I_{DS} = 11\text{A}$
$I_{BS(S)}$ Zero Gate Voltage Drain Current	ALL	—	—	250	μA	$V_{DS} = \text{Max. Rating}, V_{GS} = 0\text{V}$
		—	—	1000		$V_{DS} = 0.8 \times \text{Max. Rating}$ $V_{GS} = 0\text{V}, T_J = 125^\circ\text{C}$
I_{GS} Gate-to-Source Leakage Forward	ALL	—	—	500	nA	$V_{GS} = 20\text{V}$
I_{GS} Gate-to-Source Leakage Reverse	ALL	—	—	-500	nA	$V_{GS} = -20\text{V}$
Q_g Total Gate Charge	ALL	—	40	60	nC	$V_{GS} = 10\text{V}, I_D = 18\text{A}$
Q_{gs} Gate-to-Source Charge	ALL	—	6.9	10	nC	$V_{DS} = 0.8 \times \text{Max. Rating}$
Q_{gd} Gate-to-Drain ("Miller") Charge	—	—	21	32	nC	See Fig. 16 (Independent of operating temperature)
$t_{d(on)}$ Turn-On Delay Time	ALL	—	14	21	ns	$V_{DD} = 100\text{V}, I_D = 18\text{A}, R_G = 9.1\Omega$ $R_D = 5.6\Omega$ See Fig. 15 (Independent of operating temperature)
t_r Rise Time	ALL	—	51	77	ns	
$t_{d(off)}$ Turn-Off Delay Time	ALL	—	45	68	ns	
t_f Fall Time	ALL	—	36	54	ns	
L_D Internal Drain Inductance	ALL	—	4.5	—	nH	Measured from the drain lead, 6mm (0.25 in.) from package to center of die.
L_S Internal Source Inductance	ALL	—	7.5	—	nH	Measured from the source lead, 6mm (0.25 in.) from package to source bonding pad.
C_{iss} Input Capacitance	ALL	—	1300	—	pF	$V_{GS} = 0\text{V}, V_{DS} = 25\text{V}$ $f = 1.0 \text{ MHz}$
C_{oss} Output Capacitance	ALL	—	380	—	pF	
C_{rss} Reverse Transfer Capacitance	ALL	—	93	—	pF	See Fig. 10



INTERNATIONAL RECTIFIER


Source-Drain Diode Ratings and Characteristics

Parameter	Type	Min.	Typ.	Max.	Units	Test Conditions
I_S Continuous Source Current (Body Diode)	ALL	—	—	20	A	Modified MOSFET symbol showing the integral Reverse p-n junction rectifier.
I_{SM} Pulsed Source Current (Body Diode) ①	ALL	—	—	80	A	
V_{SD} Diode Forward Voltage ②	ALL	—	—	2.0	V	$T_J = 25^\circ\text{C}$, $I_S = 18\text{A}$, $V_{GS} = 0\text{V}$
t_{fr} Reverse Recovery Time	ALL	120	250	530	ns	$T_J = 25^\circ\text{C}$, $I_F = 18\text{A}$, $dI/dt = 100 \text{ A}/\mu\text{s}$
Q_{RR} Reverse Recovery Charge	ALL	1.3	2.6	5.6	μC	
t_{on} Forward Turn-On Time	ALL	Intrinsic turn-on time is negligible. Turn-on speed is substantially controlled by $L_S + L_D$.				



Thermal Resistance

R_{thJC} Junction-to-Case	ALL	—	—	0.83	K/W③	
R_{thCS} Case-to-Sink	ALL	—	0.24	—	K/W④	Mounting surface flat, smooth, and greased
R_{thJA} Junction-to-Ambient	ALL	—	—	40	K/W⑤	Typical socket mount
Mounting Torque	ALL	—	—	10	In. • lbs.	Standard 6-32 screw



① Repetitive Rating; Pulse width limited by maximum junction temperature (see figure 5)
Refer. to current HEXFET reliability report

③ $I_{SD} \leq 20\text{A}$, $dI/dt \leq 160 \text{ A}/\mu\text{s}$,
 $V_{DD} \leq BV_{DSS}$, $T_J \leq 150^\circ\text{C}$
Suggested $R_G = 9.1\Omega$

⑤ K/W = °C/W
W/K = W/°C

② @ $V_{DD} = 50\text{V}$, Starting $T_J = 25^\circ\text{C}$,
 $L = 1.9\text{mH}$, $R_G = 25\Omega$, Peak $I_L = 20\text{A}$

④ Pulse width $\leq 300 \mu\text{s}$; Duty Cycle $\leq 2\%$




Fig. 1 — Typical Output Characteristics




Fig. 2 — Typical Transfer Characteristics

IRFP240, IRFP241, IRFP242, IRFP243 Devices

LIE D 4855452 0008737 0

INTERNATIONAL RECTIFIER

T-39-13




Fig. 3 — Typical Saturation Characteristics




Fig. 4 — Maximum Safe Operating Area




Fig. 5 — Maximum Effective Transient Thermal Impedance, Junction-to-Case Vs. Pulse Duration

INTERNATIONAL RECTIFIER




Fig. 6 — Typical Transconductance Vs. Drain Current




Fig. 7 — Typical Source-Drain Diode Forward Voltage




Fig. 8 — Breakdown Voltage Vs. Temperature




Fig. 9 — Normalized On-Resistance Vs. Temperature

IRFP240, IRFP241, IRFP242, IRFP243 Devices

INTERNATIONAL RECTIFIER

11E D 4855452 0008739 3

T-39-13




Fig. 10 — Typical Capacitance Vs. Drain-to-Source Voltage




Fig. 11 — Typical Gate Charge Vs. Gate-to-Source Voltage




Fig. 12 — Typical On-Resistance Vs. Drain Current




Fig. 13 — Maximum Drain Current Vs. Case Temperature

11E D 4855452 0008740 0

INTERNATIONAL RECTIFIER




Fig. 14a — Unclamped Inductive Test Circuit




Fig. 14b — Unclamped Inductive Waveforms




Fig. 14c — Maximum Avalanche Energy Vs. Starting Junction Temperature




Fig. 15a — Switching Time Test Circuit




Fig. 15b — Switching Time Waveforms




Fig. 16a — Basic Gate Charge Waveform





Fig. 16b — Gate Charge Test Circuit

11E D 4855452 0008741 1 INTERNATIONAL RECTIFIER

Fig. 17 — Peak Diode Recovery dv/dt Test Circuit