



## SPECIFICATIONS

| Specifications            | UTD2102HM                            | UTD2102CM |
|---------------------------|--------------------------------------|-----------|
| Channels                  | 2                                    |           |
| Bandwidth                 | 100MHz                               | 100MHz    |
| Sample Rate               | 1GS/s                                |           |
| Rise Time                 | ≤3.5ns                               | ≤3.5ns    |
| Memory Depth              | 8Mpts                                | 16Mpts    |
| Waveform Acquisition Rate | ≥150000wfms/s                        |           |
| Vertical Sensitivity      | 2mV/div~10V/div                      |           |
| Time-Based Range          | 2ns/div~50s/div                      |           |
| Storage                   | Setup, Wave, Bitmap, CSV             |           |
| Trigger Modes             | Edge, Pluse, Video, Slope, Alternate |           |
| Interface                 | USB Device, USB Host, Pass/Fail      |           |

## GENERAL CHARACTERISTICS

|                              |                                                                 |
|------------------------------|-----------------------------------------------------------------|
| Power                        | 100-240VAC, 40-440Hz                                            |
| Display                      | 7 Inches 64K Color TFT LCD, (800×480)                           |
| Product Color                | Red and Gray                                                    |
| Product Net Weight           | 2.9Kg                                                           |
| Product Size                 | 330mm × 155mm × 130mm                                           |
| Standard Accessories         | Probe×2(1×,10× switchable),Power Cord ,USB Cable,PC Software CD |
| Standard Individual Packing  | Gift Box, English Manual                                        |
| Standard Quantity Per Carton | 2 PCs                                                           |
| Standard Carton Measurement  | 450mm × 420mm × 280mm (0.053 CBM Per Standard Carton)           |
| Standard Carton Gross Weight | 10Kg                                                            |
| Optional Accessories         | LAN Communication Port, RS-232 Cable                            |