



element14

EN - For pricing and availability in your local country please visit one of the below links:

DE - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

FR - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

[1N4744A-TP](#)

[1N4749A-TP](#)

[1N4728A-TP](#)

[1N4746A-TP](#)

EN

This Datasheet is presented by
the manufacturer

DE

Dieses Datenblatt wird vom
Hersteller bereitgestellt

FR

Cette fiche technique est
présentée par le fabricant



Micro Commercial Components

Micro Commercial Components
20736 Marilla Street Chatsworth
CA 91311
Phone: (818) 701-4933
Fax: (818) 701-4939

1N4728 THRU 1N4761

**1.0 Watt
Zener Diode
3.3 to 75 Volts**

Features

- Hermetic Glass Package
- Silicon Planar Zener Diodes
- These diodes are also available in the MELF case with type designation DL4728 thru DL4761

Mechanical Data

- Case: DO-41 Molded Glass
- Marking : Cathode band and type number
- Weight: 0.378 grams (Approx.)

Maximum Ratings

- Operating Temperature: -65°C to +200°C
- Storage Temperature: -65°C to +200°C
- For capacitive load, derate current by 20%

Electrical Characteristics @ 25°C Unless Otherwise Specified

DC Power Dissipation	P_d	1.0W	$T_A \leq 50^\circ\text{C}$
Peak Forward Surge Current	I_{FSM}	See Page 2	
Thermal Resistance	$R_{\theta JA}$	100°C/W	Note 1
Power Derating from 100°C	P_{tot}	10mW/°C	

Note: (1) Valid provided that electrodes at a distance of 10mm from case are kept at ambient temperature.

DO-41G

DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.166	0.205	4.10	7.60	
B	0.080	0.107	2.00	3.60	Diameter
C	0.026	0.034	0.70	0.90	Diameter
D	1.000	-----	25.40	-----	

1N4728 thru 1N4761



Electrical Characteristics (T_A = 25°C unless otherwise noted). Maximum V_F = 1.2V at I_F = 200mA

MCC PART NUMBER	ZENER VOLTAGE V _Z VOLTS	TEST CURRENT I _{ZT} mA	MAXIMUM DYNAMIC IMPEDANCE Z _{ZT} @ I _{ZT} OHMS	MAXIMUM REVERSE CURRENT I _R @ V _R μA	TEST VOLTAGE V _R VOLTS	MAXIMUM KNEE IMPEDANCE Z _{ZK} @ I _{ZK} OHMS	TEST CURRENT I _{ZK} mA
1N4728	3.3	76	10	100	1	400	1.0
1N4729	3.6	69	10	100	1	400	1.0
1N4730	3.9	64	9	50	1	400	1.0
1N4731	4.3	58	9	10	1	400	1.0
1N4732	4.7	53	8	10	1	500	1.0
1N4733	5.1	49	7	10	1	550	1.0
1N4734	5.6	45	5	10	2	600	1.0
1N4735	6.2	41	2	10	3	700	1.0
1N4736	6.8	37	3.5	10	4	700	1.0
1N4737	7.5	34	4.0	10	5	700	0.5
1N4738	8.2	31	4.5	10	6	700	0.5
1N4739	9.1	28	5.0	10	7	700	0.5
1N4740	10	25	7	10	7.6	700	0.25
1N4741	11	23	8	5	8.4	700	0.25
1N4742	12	21	9	5	9.1	700	0.25
1N4743	13	19	10	5	9.9	700	0.25
1N4744	15	17	14	5	11.4	700	0.25
1N4745	16	15.5	16	5	12.2	700	0.25
1N4746	18	14	20	5	13.7	750	0.25
1N4747	20	12.5	22	5	15.2	750	0.25
1N4748	22	11.5	23	5	16.7	750	0.25
1N4749	24	10.5	25	5	18.2	750	0.25
1N4750	27	9.5	35	5	20.6	750	0.25
1N4751	30	8.5	40	5	22.8	1000	0.25
1N4752	33	7.5	45	5	25.1	1000	0.25
1N4753	36	7.0	50	5	27.4	1000	0.25
1N4754	39	6.5	60	5	29.7	1000	0.25
1N4755	43	6.0	70	5	32.7	1500	0.25
1N4756	47	5.5	80	5	35.8	1500	0.25
1N4757	51	5.0	95	5	38.8	1500	0.25
1N4758	56	4.5	110	5	42.6	2000	0.25
1N4759	62	4.0	125	5	47.1	2000	0.25
1N4760	68	3.7	150	5	51.7	2000	0.25
1N4761	75	3.3	175	5	56.0	2000	0.25

- Note**
- 1: The JEDEC type number shown with an A suffix have a 5% tolerance on nominal zener voltage. No suffix signifies a 10% tolerance, C signifies 2%, and D suffix signifies 1% tolerance.
 - 2: The Zener impedance is derived from the 60 Hz ac voltage, which results when an ac current having an rms value equal to 10% of the DC Zener current(I_{ZT} or I_{ZK}) is superimposed on I_{ZT} or I_{ZK}. Zener impedance is measured at two points to insure a sharp knee on the breakdown curve and eliminate unstable units.
 - 3: The reverse surge current is measured at 25°C ambient using a 1/2 square wave or equivalent sine wave pulse 1/120 second duration superimposed on I_{ZT}.
 - 4: Voltage measurements to be performed 90 seconds after application of DC current.
 - 5: RoHS Compliant already and Pb-free sticker on reel, box & carton indicated RoHS compliant.



TM

Micro Commercial Components

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp.* does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp.* and all the companies whose products are represented on our website, harmless against all damages.

*****APPLICATIONS DISCLAIMER*****

Products offer by *Micro Commercial Components Corp.* are not intended for use in Medical, Aerospace or Military Applications.



element14

EN - For pricing and availability in your local country please visit one of the below links:

DE - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

FR - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

[1N4744A-TP](#)

[1N4749A-TP](#)

[1N4728A-TP](#)

[1N4746A-TP](#)

EN

This Datasheet is presented by
the manufacturer

DE

Dieses Datenblatt wird vom
Hersteller bereitgestellt

FR

Cette fiche technique est
présentée par le fabricant