



**ELECTRICAL CHARACTERISTICS : [ Tc = 25 °C unless otherwise noted ]**

Characteristic	Symbol	Min	Typ	Max	Unit
<b>* Off Characteristics :</b>					
Collector–Emitter Sustaining Voltage (1) [ Ic =100 mAdc, IB = 0 ]	V <sub>CEO(sus)</sub>	700			Vdc
Collector Cutoff Current [ V <sub>CE</sub> = 1500 Vdc, V <sub>BE</sub> = 0 ]	I <sub>CES</sub>			1	mAdc
Emitter Base Voltage [ I <sub>E</sub> = 10mA, Ic = 0 ]	BV <sub>EBO</sub>	5			Vdc
<b>* On Characteristics (1):</b>					
DC Current Gain [ Ic = 2.0 Adc , V <sub>CE</sub> = 4.0 Vdc ]	h <sub>FE</sub>	2.25			
Collector-Emitter Saturation Voltage [ Ic = 2.0 Adc , IB = 1Adc )	V <sub>CE(sat)</sub>			5	Vdc
Base-Emitter Saturation Voltage [ Ic = 2.0 Adc , IB = 1Adc ]	V <sub>BE(sat)</sub>			1.5	Vdc
<b>Dynamic Characteristics :</b>					
Current Gain – Bandwidth Product [ Ic = 0.1Adc, V <sub>CE</sub> =5 Vdc, ftest=1.0 MHz ]	f <sub>T</sub>	---	4	--	MHz
Output Capacitance (VCB=10Vdc,IE=0,f=1MHz)	C <sub>OB</sub>	--	50	--	pF
<b>SWITCHING CHARACTERISTICS</b>					
Fall Time (Ic=2Adc,IB1=1Adc,LB=25⊛H)	tf	---	0.65	---	⊛s

(1) Pulse Test : Pulse Width =5ms , Duty Cycle < 10.0%

This datasheet has been downloaded from:

[www.DatasheetCatalog.com](http://www.DatasheetCatalog.com)

Datasheets for electronic components.